

PVC BASE PROFILES AND " CLIP-IT-ON " FINISHING PROFILE

PVC BASE PROFILES (or ECO) are extruded from 1st quality white PVC (or recycled 1st quality PVC – grey colour – for eco profiles). Their goal is to support insulation at the base of the ETICS / EIFS system in order to have a perfect straight level for the insulation blocks.





PVC BASE PROFILE (white)							
Ref.	Stock	Dimensions	Pces/ Pack	Insulation thick.			
PVC base profile 8341	S	2,00 m	10	80 mm			
PVC base profile 8394	S	2,00 m	10	100 mm			
PVC base profile 8395	S	2,00 m	10	120 mm			
PVC base profile 8396	S	2,00 m	10	140 mm			
PVC base profile 8397	S	2,00 m	10	160 mm			
PVC base profile 8398		2,00 m	10	180 mm			
PVC base profile 8399		2,00 m	10	200 mm			

PVC ECO BASE PROFILE (grey)							
Ref.	Stock	Dimensions	Pces/ Pack	Insulation thick.			
PVC ECO base profile 8441		2,00 m	10	80 mm			
PVC ECO base profile 8443		2,00 m	10	100 mm			
PVC ECO base profile 8495		2,00 m	10	120 mm			
PVC ECO base profile 8496		2,00 m	10	140 mm			
PVC ECO base profile 8497		2,00 m	10	160 mm			
PVC ECO base profile 8498		2,00 m	10	180 mm			
PVC ECO base profile 8499		2,00 m	10	200 mm			

The clip-it-on "STOP ISO GWS DUO 8235" is a PVC bellcast finishing profile to be clipped on PVC base profiles. The fibermesh on it is certified (ETAG 004) and the rendering on it can be 3 mm or 6 mm thick.



STOP ISO GWS DUO						
Ref.	Stock	Dimension	Pces/ Pack	Packs/ Pal.		
STOP ISO GWS DUO (3/6 mm) 8235		2,50 m	50	36		



BELLCAST PROFILES



The PVC finishing profiles CORNER REND PVC GWS ECO 8424 & CORNER REND PVC GWS 8124 (bellcast) with certified fibermesh (ETAG 004) on it are used to give a straight finishing to corners of balconies with ETICS / EIFS systems on it.



CORNER REND PVC GWS ECO						
Ref.	Stock	Dimension	Pces/ Pack	Packs/ Pal.		
CORNER REND PVC GWS ECO 8424		2,50 m	50	36		

CORNER REND PVC GWS							
Ref.	Stock	Dimension	Pces/ Pack	Packs/ Pal.			
CORNER REND PVC GWS 8124	S	2,50 m	25	24			



ASK FOR OUR OTHER DOCUMENTATION


Our posters related to our different product lines, including Facade Insulation Systems (ETICS / EIFS)



MDB Profil catalog



APU catalog



Dealer:

info@mdb.eu www.mdbprofil.com

Quai Vercour , 98 • B-4000 LIEGE - Belgium • Tel. : 0032 (0)4 / 252 70 35 • Fax : 0032 (0)4 / 252 11 03

PROFILES FOR FACADE INSULATION SYSTEMS (ETICS / EIFS)



PVC RANGE



ANGLE BEADS

WINDOW / DOOR FINISHING PROFILES

STOP BEADS



"PER PVC GWS" is a PVC angle bead with certified (ETAG 004) fibermesh on it, in order to get a straight and perfect finishing on the corners of ETICS / EIFS systems. Fibermesh is available in different dimensions: $10 \times 15 \text{ cm}$, $10 \times 23 \text{ cm}$, and $10 \times 30 \text{ cm}$ (other dimensions on demand).



Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
PER PVC GWS 8213*	S	2,50 m	50	24

* White fibermesh - 10 x 15 cm



Min. plaster thickness: 3 mm



Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
PER PVC (ECO 841		2,50 m	50	24

* White fibermesh - 10 x 15 cm



Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
PER PVC GWS 8211*	S	2,50 m	50	24

* Blue fibermesh - 10 x 15 cm



Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
PER PVC GWS 8212*	S	2,50 m	50	24

* Yellow fibermesh - 10 x 15 cm



Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
PER PVC GWS 8214*	S	2,50 m	50	24

* Orange fibermesh - 10 x 15 cm



Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
PER PVC GWS 8219*	S	2,50 m	25	24

* White fibermesh - 10 x 23 cm





* White fibermesh - 10 x 30 cm


GWS 8220*




- protect the frame of the window/door while rendering;
- air and water insulation thanks to the PE foam;
- rendering guide to have the perfect plaster thickness (6 mm).









Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
PROFI INTER GWS LIPPE 8808*	S	2,40 m	25	24

* White fibermesh - 10 cm

Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
PROFI INTER GWS 8167 *		2,40 m	50	48


* White fibermesh – 10 cm

- "PROFI MINI GWS" is availabe with (PROFI MINI GWS LIPPE 8809) or without (PROFI MINI GWS 8168) soft finishing lip. This PVC profile with a certified (ETAG 004) fibermesh on it has 3 goals:
- protect the frame of the window/door while rendering;
- air and water insulation thanks to the PE foam;

Stock


Dim.

- rendering guide to have the perfect plaster thickness (9 mm).



PROFI MINI GWS

LIPPE 8809*



Min. plaster thickness: 9 mm

Pces/ Packs/

Pack

Pal.

Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
PROFI MINI GWS 8168 *		2,40 m	50	24

 "STOP PVC GWS" is a PVC stop bead with certified (ETAG 004) white fibermesh on it, in order to get a straight finishing line on ETICS / EIFS systems. Min. plaster thickness: 3 mm, up to 15 mm.





10 mm

Pack

25

Pces/ Packs/



* Min. plaster thickness: 3 mm

Stock

* Min. plaster thickness: 10 mm

Stock

Dim.

2,50 m




* Min. plaster thickness : 6 mm

2,50 m



GWS 8704 *



25

Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
STOP PVC GWS 8706 *		2,50 m	25	24

* Min. plaster thickness: 15 mm

MOVEMENT BEADS

Movement beads are used to avoid crackings between two building components or for big surfaces of insulation.



Ref.

DILAT PVC


GWS "V" 8034 *

Ref.


STOP PVC

GWS 8705 *









Ref.	Stock	Dim.	Pces/ Pack	Packs/ Pal.
DILAT PVC GWS "E" 8035 *	S	2,50 m	25	16